Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 *Version number 1* *Revision: 07/28/2026*

1 Identification

· ***Product identifier***

· ***Trade name:*** **PERI Sealing adhesive 4 component B**

· ***Other means of identification***

· ***Application of the substance / the mixture***
Hardening agent/ Curing agent
Curing agent/ cross-linker/ Vulcanizing agent

· ***Details of the supplier of the safety data sheet***

· ***Manufacturer/Supplier:***
PERI Formwork Systems, Inc. Canada
45 Nixon Road
Bolton
Ontario L7E 1K1
Canada

· ***Information department:***
Telephone: +1 905 951-5400
Fax: +1 905 951-5454
E-Mail: info@peri.ca
www.PERI.ca

· ***Emergency telephone number:***
Poison and Drug Information Services Calgary
+1 800 332 1414 (Alberta, NW Territories)
+1 866 454 1212 (Saskatchewan)
+1 403 944 1414 (Calgary, outside Alberta, VOIP users)

2 Hazard identification

· ***Classification of the substance or mixture***


GHS05 Corrosion

Skin Corrosion - Category 1B	H314 Causes severe skin burns and eye damage.
Eye damage/irritation – Category 1	H318 Causes serious eye damage.


GHS07

Sensitization - skin – Category 1A	H317 May cause an allergic skin reaction.

· ***Additional information:***
The full text of the classification and labeling elements mentioned is given in Section 16.

· ***Label elements***

· ***GHS label elements***
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 1)

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Isophorone diamine
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)
Benzyl alcohol

· **Hazard statements**
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

· **Precautionary statements**

P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

· **Information pertaining to particular dangers for man and environment:**
· **Classification system:**
· **HMIS-ratings (scale 0 - 4)**

HEALTH	*3
FIRE	1
REACTIVITY	0

Health = *3
Fire = 1
Reactivity = 0

3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**
· **Description:**
amine hardener
Crosslinker

(Contd. on page 3)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 *Version number 1* *Revision: 07/28/2026*

***Trade name:* PERI Sealing adhesive 4 component B**

(Contd. of page 2)

· ***Dangerous components:***		
CAS: 100-51-6 RTECS: DN 3150000	Benzyl alcohol	5 - 10% w/w *
CAS: 2855-13-2 RTECS: GV 5020833	Isophorone diamine	5 - 10% w/w *
CAS: 113930-69-1	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	5 - 10% w/w *

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

· ***Description of first aid measures***
· ***General information:*** Immediately remove any clothing contaminated by the product.
· ***After inhalation:***
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
· ***After skin contact:***
Immediately wash with water and soap and rinse thoroughly.
Call a doctor immediately.
Wash contaminated clothing before re-use.
Discard contaminated shoes.
· ***After eye contact:***
Keep eye lids open and rinse them with ample amounts of clean running water for at least 15 minutes.
Call a doctor immediately.
· ***After swallowing:***
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.
· ***Most important symptoms and effects, both acute and delayed*** No further relevant information available.
· ***Indication of any immediate medical attention and special treatment needed***
No further relevant information available.

5 Fire-fighting measures

· ***Extinguishing media***
· ***Suitable extinguishing agents:***
Foam, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· ***For safety reasons unsuitable extinguishing agents:*** Water with full jet
· ***Special hazards arising from the substance or mixture***
During heating or in case of fire poisonous gases are produced.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)

(Contd. on page 4)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 3)

· ***Advice for firefighters***
· ***Protective equipment:***
In case of fire wear breathing equipment being independent of ambient air and suit provided full protection against chemicals.
· ***Additional information***
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· ***Personal precautions, protective equipment and emergency procedures***
Keep people at a distance and stay upwind.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
· ***For non-emergency personnel*** Avoid contact with the product.
· ***For emergency responders*** Put on suitable personal protective equipment.
· ***Environmental precautions:***
Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
· ***Methods and material for containment and cleaning up:***
Absorb with liquid-binding material (sand, diatomite, universal binders) and disposal in suitable containers.
Dispose contaminated material as waste according to section 13.
· ***Reference to other sections***
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· ***Precautions for safe handling***
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Avoid release to the environment.
· ***Information about protection against explosions and fires:*** No special measures required.

· ***Handling:***
Avoid contact with eyes and skin.
Wash thoroughly after handling.
Wash contaminated clothing before re-use.

(Contd. on page 5)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 4)

· ***Conditions for safe storage, including any incompatibilities***
· ***Storage:***
· ***Requirements to be met by storerooms and receptacles:***
Store in a cool location.
Recommended storage temperature: 10°C to 30°C.
Store only in the original receptacle.
· ***Information about storage in one common storage facility:***
Store away from oxidizing agents.
Store away from foodstuffs.
· ***Further information about storage conditions:*** Store receptacle in a well ventilated area.
· ***Specific end use(s)*** No further relevant information available.

8 Exposure controls/ Personal protection

· ***Control parameters***
· ***Components with limit values that require monitoring at the workplace:***
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
· ***Additional information:*** The lists that were valid during the creation were used as basis.

· ***Exposure controls***
· ***Appropriate engineering controls***
Care for good ventilation, i.e. by local exhaust or general exhaust ventilation. If this is not sufficient to keep the concentration of solvent vapours below workplace threshold values an appropriate protective breathing apparatus shall be worn.
· ***Personal protective equipment:***
· ***General protective and hygienic measures:***
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· ***Breathing equipment:***
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Filter A/P2
· ***Protection of hands:***



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 5)

· ***Material of gloves***
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· ***Penetration time of glove material***
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· ***For the permanent contact gloves made of the following materials are suitable:***
Fluorocarbon rubber (Viton)
In case of a layer thickness of 0.4 mm the penetration time is longer than 30 minutes.
· ***For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:***
Butyl rubber, BR
Nitrile rubber, NBR
· ***Eye protection:***



Tightly sealed goggles

· ***Body protection:***



Protective work clothing

9 Physical and chemical properties

· ***Information on basic physical and chemical properties***	
· ***General Information***	
· ***Color:***	Pigmented
· ***Odor:***	Amine-like
· ***Melting point/Melting range:***	Undetermined
· ***Boiling point/Boiling range:***	Undetermined
· ***Explosion limits:***	
· ***Lower:***	Not determined
· ***Upper:***	Not determined
· ***Flash point:***	114 °C (calculated)
· ***Auto igniting:***	Product is not selfigniting.
· ***SADT***	
· ***pH-value:***	Not determined

(Contd. on page 7)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 6)

· **Viscosity:**	
· **Kinematic:**	Not determined
· **Dynamic at 25 °C:**	204200 - 306200 mPas (ISO 3219)
· **Solubility in / Miscibility with**	
· **Water:**	Not determined
· **Vapor pressure:**	Not determined
· **Density at 20 °C:**	2 g/cm³ (ISO 2811-1)
· **Particle characteristics**	Not applicable

· **Other information**	
· **Appearance:**	
· **Form:**	Pasty
· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **Possibility of hazardous reactions** Reacts with strong acids and oxidizing agents.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:**
Ammonia
Carbon monoxide and carbon dioxide
Organic decomposition products

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
ATE (Acute Toxicity Estimate)		
Oral	LD50	> 5,543 - 11,085 mg/kg

CAS: 100-51-6 Benzyl alcohol		
Oral	LD50	1,200 mg/kg (ATE) 1,620 mg/kg (Rat)

(Contd. on page 8)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 7)

Dermal	LD50	2,000 mg/kg (Rabbit)
Inhalative	LC50	> 4,178 mg/l/4h (Rat) (OECD 403)
CAS: 2855-13-2 Isophorone diamine		
Oral	LD50	1,030 mg/kg (Rat) (OECD 401)
Dermal	LD50	> 2,000 mg/kg (Rat) (OECD 402)

· ***Primary irritant effect:***
· ***on the skin:*** Caustic effect on skin and mucous membranes.
· ***on the eye:*** Strong caustic effect.
· ***Sensitization:*** Sensitization possible through skin contact.
· ***Additional toxicological information:***
The product shows the following dangers according to internally approved calculation methods for preparations:
Toxic
Corrosive
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· ***Carcinogenic categories***

· ***IARC (International Agency for Research on Cancer)***		
CAS: 9002-88-4	Polyethylene	3

· ***NTP (National Toxicology Program)***
None of the ingredients is listed.

12 Ecological information

· ***Toxicity***

· ***Aquatic toxicity:***	
CAS: 100-51-6 Benzyl alcohol	
EC50	230 mg/l/48h (Daphnia magna) (OECD 202)
LC50 (static)	460 mg/l/96h (Pimephales promelas) (EPA OPP 72-1)
EC50 (static)	770 mg/l/72h (Raphidocelis subcapitata)
CAS: 2855-13-2 Isophorone diamine	
EC50 (static)	23 mg/l/48h (Daphnia magna) (OECD 202)
LC50 (static)	110 mg/l/96h (fish) (EU C.1)
EC50 (static)	37 mg/l/72h (Desmodesmus subspicatus) (EU C.3)

· ***Persistence and degradability*** The polymeric portion of the product is heavily eliminable.
· ***Bioaccumulative potential*** No further relevant information available.
· ***Mobility in soil*** No further relevant information available.

(Contd. on page 9)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 8)

· ***Results of PBT and vPvB assessment***
· ***PBT:*** Not applicable
· ***vPvB:*** Not applicable
· ***Other adverse effects***
· ***Remark:*** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
· ***Additional ecological information:***
· ***General notes:***
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

· ***Waste treatment methods***
· ***Recommendation:***
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· ***Uncleaned packagings:***
· ***Recommendation:***
Dispose of packaging according to regulations on the disposal of packagings.
Non contaminated packagings can be recycled.
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transport information

· ***UN-Number***	
· ***DOT/TDG, ADR, IMDG, IATA***	UN2735
· ***UN proper shipping name***	
· ***DOT/TDG, ADR***	Polyamines, liquid, corrosive, n.o.s. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine), Isophoronediamine)
· ***IMDG, IATA***	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine), ISOPHORONEDIAMINE)

(Contd. on page 10)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 | Version number 1 | Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT/TDG (Transport dangerous goods):**



· **Class**	8 Corrosive substances
· **Label**	8

· **ADR**



· **Class**	8 (C7) Corrosive substances
· **Label**	8

· **IMDG, IATA**



· **Class**	8 Corrosive substances
· **Label**	8

· **Packing group**	
· **DOT/TDG, ADR, IMDG, IATA**	II
· **Environmental hazards:**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT/TDG**	
· **Quantity limitations**	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· **ADR**	
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 Version number 1 Revision: 07/28/2026

Trade name: PERI Sealing adhesive 4 component B

(Contd. of page 10)

· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Special precautions for user**	Warning: Corrosive substances
· **Hazard identification number (Kemler code):**	80
· **EMS Number:**	F-A,S-B
· **Segregation groups**	(SGG18) Alkalis
· **Stowage Category**	A
· **Segregation Code**	SG35 Stow "separated from" SGG1-acids
· **UN "Model Regulation":**	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**
All ingredients are listed.

· **Canadian Non-Domestic Substances List (NDSL)**
None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**
None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

CAS: 100-51-6	Benzyl alcohol

(Contd. on page 12)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 07/28/2026 *Version number 1* *Revision: 07/28/2026*

***Trade name:* PERI Sealing adhesive 4 component B**

(Contd. of page 11)

CAS: 2855-13-2	Isophorone diamine

· ***Per- and polyfluoroalkyl substances (PFAS)***

None of the ingredients is listed.

· ***National regulations:***

· ***Information about limitation of use:***
Employment restrictions concerning women of child-bearing age must be observed.
Employment restrictions concerning young persons must be observed.

· ***Chemical safety assessment:*** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· ***Date of preparation*** 07/28/2026

· ***Abbreviations and acronyms:***
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative