

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name:** Peri sealing adhesive 4 - Silipox B

· **UFI:** 9ND0-K07D-A00W-2V60

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture**

Hardening agent/ Curing agent

Curing agent/ cross-linker/ Vulcanising agent

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

PERI SE

Rudolf-Diesel-Straße 19

89264 Weißenhorn

Deutschland

· **Informing department:**

Telefon: +49 (0)7309.950-0

Fax: +49 (0)7309.951-0

E-mail: info@peri.com

URL: www.peri.com

· 1.4 Emergency telephone number:

Gift-Informationszentrum Nord, Göttingen

Poison Information Center, Göttingen

Tel.: +49 (0)551 19240

(German and English only)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B

H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.



GHS07

Skin Sens. 1

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

isophorone diamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)
benzyl alcohol

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description:

amine hardener

Crosslinker

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 2)

· Dangerous components:		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-X	benzyl alcohol ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1B, H317 ATE: LD50 oral: 1,200 mg/kg	≥ 2.5 - < 10%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-X	isophorone diamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥ 5 - ≤ 10%
CAS: 113930-69-1 NLP: 500-302-7	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	≥ 5 - < 10%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
 - **General information** Instantly remove any clothing contaminated by the product.
 - **After inhalation**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness bring patient into stable side position for transport.
 - **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
Call a doctor immediately.
Wash contaminated clothing before re-use.
Discard contaminated shoes.
 - **After eye contact**
Keep eye lids open and rinse them with ample amounts of clean running water for at least 15 minutes.
Call a doctor immediately.
 - **After swallowing**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents**
Extinguishing powder, foam or water jet. Fight larger fires with water jet or alcohol-resistant foam.
 - **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
 - **5.2 Special hazards arising from the substance or mixture**
Formation of poisonous gases during heating or in fires.
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)
 - **5.3 Advice for firefighters**
 - **Protective equipment:**
In case of fire wear breathing equipment being independent of ambient air and suit provided full protection against chemicals.
 - **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
-

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep people at a distance and stay on the windward side.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
 - **6.2 Environmental precautions:**
Inform respective authorities in case product reaches water or sewage system.
Do not allow to enter drainage system, surface or ground water.
 - **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, universal binders) and disposal in suitable containers.
Dispose of contaminated material as waste according to section 13.
 - **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.
-

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep containers tightly sealed.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
 - **Requirements to be met by storerooms and containers:**
 - Store in cool location.
 - Recommended storage temperature: 10°C to 30°C.
 - Store only in the original container.
 - **Information about storage in one common storage facility:**
 - Store away from oxidising agents.
 - Store away from foodstuffs.
 - **Further information about storage conditions:** Store container in a well ventilated position.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
CAS: 100-51-6 benzyl alcohol		
Oral	DNEL (consumer, short-term, systemic)	20 mg/kg bw/day (human)
	DNEL (consumer, long-term, systemic)	4 mg/kg bw/day (human)
Dermal	DNEL (worker, short-term, systemic)	40 mg/kg bw/day (human)
	DNEL (worker, long-term, systemic)	8 mg/kg bw/day (human)
Inhalative	DNEL (consumer, short-term, systemic)	20 mg/kg bw/day (human)
	DNEL (consumer, long-term, systemic)	4 mg/kg bw/day (human)
	DNEL (worker, short-term, systemic)	110 mg/m ³ (human)
	DNEL (worker, long-term, systemic)	22 mg/m ³ (human)
	DNEL (consumer, short-term, systemic)	27 mg/m ³ (human)
	DNEL (consumer, long-term, systemic)	5.4 mg/m ³ (human)
CAS: 2855-13-2 isophorone diamine		
Oral	DNEL (consumer, long-term, systemic)	0.526 mg/kg bw/day (human)
Inhalative	DNEL (worker, short-term, local)	0.073 mg/m ³ (human)
	DNEL (worker, long-term, local)	0.073 mg/m ³ (human)
CAS: 113930-69-1 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)		
Oral	DNEL (consumer, short-term, systemic)	0.05 mg/kg bw/day (human)
Dermal	DNEL (worker, short-term, systemic)	0.14 mg/kg bw/day (human)

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 5)

Inhalative	DNEL (consumer, short-term, systemic)	0.05 mg/kg bw/day (human)
	DNEL (worker, short-term, systemic)	0.493 mg/m ³ (human)
	DNEL (consumer, short-term, systemic)	0.074 mg/m ³ (human)

· PNECs

CAS: 100-51-6 benzyl alcohol

PNEC aqua (fresh water)	1 mg/L (.)
PNEC Water (marine water)	0.1 mg/L (.)
PNEC STP - Sewage Treatment Plant	39 mg/L (.)
PNEC soil	0.456 mg/kg soil dw (.)
PNEC sediment (fresh water)	5.27 mg/kg sedim. dw (.)
PNEC sediment (marine water)	0.527 mg/kg sedim. dw (.)
PNEC Water (sporadic release)	2.3 mg/L (.)

CAS: 2855-13-2 isophorone diamine

PNEC aqua (fresh water)	0.06 mg/L (.)
PNEC Water (marine water)	0.006 mg/L (.)
PNEC STP - Sewage Treatment Plant	3.18 mg/L (.)
PNEC sediment (fresh water)	5.784 mg/kg sedim. dw (.)
PNEC sediment (marine water)	0.578 mg/kg sedim. dw (.)
PNEC Water (sporadic release)	0.23 mg/L (.)

CAS: 113930-69-1 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

PNEC aqua (fresh water)	0.001 mg/L
PNEC STP - Sewage Treatment Plant	8.889 mg/L
PNEC soil	923 mg/kg soil dw
PNEC sediment (fresh water)	4,610 mg/kg sedim. dw
PNEC sediment (marine water)	461 mg/kg sedim. dw
PNEC Water (sporadic release)	0.015 mg/L
PNEC oral	3.33 mg/kg food

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

Care for good ventilation, i.e. by local exhaust or general exhaust ventilation. If this is not sufficient to keep the concentration of solvent vapours below workplace threshold values an appropriate protective breathing apparatus shall be worn.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Take off all contaminated clothing immediately.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 6)

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter A/P2.

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

In case of a layer thickness of 0.4 mm the penetration time is longer than 30 minutes.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

· **Eye/face protection**



Tightly sealed safety glasses.

· **Body protection:**



Protective work clothing.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Pigmented
· Odour:	Amine-like
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not determined
· Lower and upper explosion limit	
· Lower:	Not determined
· Upper:	Not determined
· Flash point:	114 °C (berechnet)
· Auto-ignition temperature:	Product is not selfigniting.
· SADT	
· pH	Not determined
· Viscosity:	
· Kinematic viscosity	Not determined
· dynamic at 25 °C:	204200 - 306200 mPas (ISO 3219)
· Solubility	
· Water:	Not determined
· Partition coefficient n-octanol/water (log value)	Not determined
· Vapour pressure:	Not determined
· Density and/or relative density	
· Density at 20 °C	2 g/cm ³ (ISO 2811-1)

· 9.2 Other information

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 8)

· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong acids and oxidizing agents
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 - Ammonia
 - Carbon monoxide and carbon dioxide
 - Organic decomposition products

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	> 5,543 - 11,085 mg/kg
------	------	------------------------

CAS: 100-51-6 benzyl alcohol

Oral	LD50	1,200 mg/kg (ATE) 1,620 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50	> 4,178 mg/l/4h (Rat) (OECD 403)

CAS: 2855-13-2 isophorone diamine

Oral	LD50	1,030 mg/kg (Rat) (OECD 401)
Dermal	LD50	> 2,000 mg/kg (Rat) (OECD 402)

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 9)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**

· **Repeated dose toxicity**

CAS: 2855-13-2 isophorone diamine

Oral	NOAEL (90d)	60 mg/kg bw/day (Rat) (OECD 408)
------	-------------	----------------------------------

CAS: 113930-69-1 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

Oral	NOAEL (28d)	10 mg/kg bw/day (Rat)
Inhalative	NOAEC (2y)	12.3 mg/m ³ (Rat)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 100-51-6 benzyl alcohol

EC50	230 mg/l/48h (Daphnia magna) (OECD 202)
LC50 (static)	460 mg/l/96h (Pimephales promelas) (EPA OPP 72-1)
EC50 (static)	770 mg/l/72h (Raphidocelis subcapitata)

CAS: 2855-13-2 isophorone diamine

EC50 (static)	23 mg/l/48h (Daphnia magna) (OECD 202)
LC50 (static)	110 mg/l/96h (fish) (EU C.1)
EC50 (static)	37 mg/l/72h (Desmodesmus subspicatus) (EU C.3)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 10)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable
 - **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
 - **Remark:** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - **Additional ecological information:**
 - **General notes:**
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
The waste code numbers mentioned are recommendations based on the probable use of the product.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP8	Corrosive
HP14	Ecotoxic

- **Uncleaned packagings:**
 - **Recommendation:**
Dispose of packaging according to regulations on the disposal of packagings.
Non contaminated packagings can be used for recycling.
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

EU

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 11)

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR/RID, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR/RID, IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine), ISOPHORONEDIAMINE)
· 14.3 Transport hazard class(es) · ADR/RID	
	
· Class · Label	8 (C7) Corrosive substances. 8
· IMDG, IATA	
	
· Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR/RID, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Segregation Code	Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable

(Contd. on page 13)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 12)

· Transport/Additional information:	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· ADR/RID	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

(Contd. on page 14)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 13)

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **National regulations**

· **Information about limitation of use:**

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning women of child-bearing age must be observed.

· **Water hazard class:**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is contained.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**



This Safety Data Sheet has been drawn up in cooperation with:

DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,
phone: (+49) 511 42079 - 0, reach@dekra.com.

© DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 15)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2026

Version number 1

Revision: 05.06.2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. from page 14)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU
