

Safety Data Sheet acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

1 Identification

- **Other means of identification**
- **Trade name:** Peri sealing adhesive 4 - Silipox B
- **Application of the substance / the mixture**
Hardening agent/ Curing agent
Curing agent/ cross-linker/ Vulcanizing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
PERI USA
PERI Formwork Systems, Inc. USA
7135 Dorsey Run Road
Elkridge, MD 21075
- **Information department:**
Telephone: +1 410 712 7225
Telefax: +1 410 712 7080
E-Mail: info@peri-usa.com
URL: www.peri-usa.com
- **Emergency telephone number:**
National Capital Poison Center, U.S.A.:
1-800-222-1222
3201 New Mexico Ave Ste 310
20016 Washington, DC
USA

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin corrosion 1B H314 Causes severe skin burns and eye damage.
Eye damage 1 H318 Causes serious eye damage.



GHS07

Sensitization - skin 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 1)

· Hazard pictograms



GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Isophorone diamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

Benzyl alcohol

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

· Classification system:

· HMIS-ratings (scale 0 - 4)

HEALTH	*3	Health = *3
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable

· **vPvB:** Not applicable

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

amine hardener

Crosslinker

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 2)

· Dangerous components:		
CAS: 100-51-6 RTECS: DN 3150000	Benzyl alcohol	5 - 10% *
CAS: 2855-13-2 RTECS: GV 5020833	Isophorone diamine	5 - 10% *
CAS: 113930-69-1	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	5 - 10% *

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

· **General information:** Immediately remove any clothing contaminated by the product.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Call a doctor immediately.

Wash contaminated clothing before re-use.

Discard contaminated shoes.

· After eye contact:

Keep eye lids open and rinse them with ample amounts of clean running water for at least 15 minutes.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Foam, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 3)

· **Advice for firefighters**

· **Protective equipment:**

In case of fire wear breathing equipment being independent of ambient air and suit provided full protection against chemicals.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Keep people at a distance and stay upwind.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, universal binders) and disposal in suitable containers.

Dispose contaminated material as waste according to section 13.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 100-51-6	Benzyl alcohol	10 ppm
---------------	----------------	--------

· **PAC-2:**

CAS: 100-51-6	Benzyl alcohol	110 ppm
---------------	----------------	---------

· **PAC-3:**

CAS: 100-51-6	Benzyl alcohol	660 ppm
---------------	----------------	---------

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling**

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Recommended storage temperature: 10°C to 30°C.
 - Store only in the original receptacle.
 - **Information about storage in one common storage facility:**
 - Store away from oxidizing agents.
 - Store away from foodstuffs.
 - **Further information about storage conditions:** Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 - The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
 - At this time, the other constituents have no known exposure limits.

CAS: 100-51-6 Benzyl alcohol

WEEL Long-term value: 10 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Appropriate engineering controls**
 - Care for good ventilation, i.e. by local exhaust or general exhaust ventilation. If this is not sufficient to keep the concentration of solvent vapours below workplace threshold values an appropriate protective breathing apparatus shall be worn.
- **Personal protective equipment:**
 - **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes and skin.
 - **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
 - Filter A/P2
 - **Protection of hands:**



Protective gloves

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

In case of a layer thickness of 0.4 mm the penetration time is longer than 30 minutes.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Color:**

Pigmented

· **Odor:**

Amine-like

· **Melting point/Melting range:**

Undetermined

· **Boiling point/Boiling range:**

Undetermined

· **Explosion limits:**

· **Lower:**

Not determined

· **Upper:**

Not determined

· **Flash point:**

114 °C (237.2 °F) (berechnet)

· **Auto igniting:**

Product is not selfigniting.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 6)

· SADT	
· pH-value:	Not determined
· Viscosity:	
· Kinematic:	Not determined
· Dynamic at 25 °C (77 °F):	204200 - 306200 mPas (ISO 3219)
· Solubility in / Miscibility with	
· Water:	Not determined
· Segregation coefficient (n-octanol/water):	Not determined
· Vapor pressure:	Not determined
· Density at 20 °C (68 °F):	2 g/cm ³ (16.69 lbs/gal) (ISO 2811-1)
· Particle characteristics	Not applicable
· Other information	
· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· VOC USA	
· VOC content:	0.00 %

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
 - **Possibility of hazardous reactions** Reacts with strong acids and oxidizing agents.
 - **Conditions to avoid** No further relevant information available.
 - **Incompatible materials:** No further relevant information available.
 - **Hazardous decomposition products:**
 - Ammonia
 - Carbon monoxide and carbon dioxide
 - Organic decomposition products

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:	
ATE (Acute Toxicity Estimate)	
Oral	LD50 > 5,543 - 11,085 mg/kg

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 7)

CAS: 100-51-6 Benzyl alcohol		
Oral	LD50	1,200 mg/kg (ATE) 1,620 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)
Inhalative	LC50	> 4,178 mg/l/4h (Rat) (OECD 403)
CAS: 2855-13-2 Isophorone diamine		
Oral	LD50	1,030 mg/kg (Rat) (OECD 401)
Dermal	LD50	> 2,000 mg/kg (Rat) (OECD 402)

- **Primary irritant effect:**
- **on the skin:**
Causes severe skin burns and eye damage.
- **on the eye:**
Causes serious eye damage.
- **Sensitization:**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **Specific target organ toxicity - single exposure**
Based on available data, the classification criteria are not met.
- **Specific target organ toxicity - repeated exposure**
Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.
· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:	
CAS: 100-51-6 Benzyl alcohol	
EC50	230 mg/l/48h (Daphnia magna) (OECD 202)

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 8)

LC50 (static)	460 mg/l/96h (Pimephales promelas) (EPA OPP 72-1)
EC50 (static)	770 mg/l/72h (Raphidocelis subcapitata)
CAS: 2855-13-2 Isophorone diamine	
EC50 (static)	23 mg/l/48h (Daphnia magna) (OECD 202)
LC50 (static)	110 mg/l/96h (fish) (EU C.1)
EC50 (static)	37 mg/l/72h (Desmodesmus subspicatus) (EU C.3)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable
 - **vPvB:** Not applicable
- **Other adverse effects**
 - **Remark:** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Additional ecological information:**
 - **General notes:**
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:**
 - Dispose of packaging according to regulations on the disposal of packagings.
 - Non contaminated packagings can be recycled.
 - Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transport information

· UN-Number	
· DOT, ADR/RID, IMDG, IATA	UN2735
· UN proper shipping name	

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 9)

· DOT · ADR/RID, IMDG, IATA	Amines, liquid, corrosive, n.o.s. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine), Isophoronediamine) AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine), ISOPHORONEDIAMINE)
· Transport hazard class(es) · DOT	
 · Class · Label	8 Corrosive substances 8
· ADR/RID	
 · Class · Label	8 (C7) Corrosive substances 8
· IMDG, IATA	
 · Class · Label	8 Corrosive substances 8
· Packing group · DOT, ADR/RID, IMDG, IATA	II
· Environmental hazards:	Not applicable
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Segregation groups · Stowage Category	Warning: Corrosive substances 80 F-A,S-B (SGG18) Alkalis A

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 10)

· Segregation Code	SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· ADR/RID	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, REACTION PRODUCTS WITH M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
None of the ingredient is listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
· Hazardous Air Pollutants
None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 11)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

CAS: 100-51-6 Benzyl alcohol

CAS: 2855-13-2 Isophorone diamine

· Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

CAS: 100-51-6 Benzyl alcohol

CAS: 2855-13-2 Isophorone diamine

· National regulations:

· Information about limitation of use:

Employment restrictions concerning women of child-bearing age must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 13)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 06/05/2026

Version number 1

Reviewed on 06/05/2026

Trade name: Peri sealing adhesive 4 - Silipox B

(Contd. of page 12)

· Department issuing SDS:

This Safety Data Sheet has been drawn up in cooperation with:
DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,
phone: (+49) 511 42079 - 0, reach@dekra.com.

© DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.

· Date of preparation 06/05/2026**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin corrosion 1B: Skin corrosion/irritation – Category 1B

Eye damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - skin 1: Skin sensitisation – Category 1